

Standard Colors:



Red



Blue

Buzzaround 3 wheel GB121B-STD 4 wheel GB124A-STD



The next generation of the popular Buzzaround scooter series is now available! The Buzzaround XL offers improved standard features to make your riding experience better than ever. It features a larger wraparound Delta tiller, higher ground clearance of 3.5", and an increased operating range of up to 10 miles on the standard 12 AH batteries. Upgrade with the new XR Extended Range Battery option for even more mileage! The Buzzaround XL also offers a new stylish, contoured stadium style seat for more comfort and increased seating tolerance. This scooter disassembles in seconds with just four easy steps making transporting it from one destination to another a breeze!



Features:

- 300 lb. Weight Capacity
- Improved Drivability
- Increased Operating Range
- Higher Ground Clearance
- LED Angle-adjustable Headlight
- USB Port on the Tiller
- Phone & Cup Holders
- Quick & Easy Disassembly

Upgrade with NEW XR Extended Range Battery Option!

(Packaged separately as an accessory but ships with the unit.)



| Item | GB121B-STD | GB124A-STD |
|--|--------------------------|--------------------|
| Description | XL | XL |
| Medicare Code | K0800 | K0800 |
| Weight Capacity | 300 lbs. | 300 lbs. |
| Drive Wheels | Rear | Rear |
| Maximum Speed | 4 mph | 4 mph |
| Operating Range up to ¹ | 10 miles/18 miles | 10 miles/18 miles |
| Under Deck Clearance | 3.5" | 3.5" |
| Turning Radius | 37.5" | 45.5" |
| Type Batteries | 2-12AH / 2-22AH | 2-12AH / 2-22AH |
| Colors | Red, Blue | Red, Blue |
| Freewheel Mode | Yes | Yes |
| Electronic Speed Control | Yes | Yes |
| Electro-Mechanical Brake | s Yes | Yes |
| Charger | Off-board | Off-board |
| Controller | 50 Amp | 50 Amp |
| Dimensions | | |
| Length | 41" | 40" |
| Width | 20" | 20" |
| Height (ground to top of back of seat) | 33.75"-35.25" | 33.75"-35.25" |
| Ground to Top of Seat | 21.75"-23.25" | 21.75"-23.25" |
| Ground to Top of Deck | 5" | 5" |
| Deck to Top of Seat | 16.5"-18" | 16.5"-18" |
| Number of Seat Height Po | ositions 3 | 3 |
| Size of Increments | .75" | .75" |
| Front Axle to Rear Axle | 31.5" | 30.50" |
| Weight of Unit: (assemble | ed) ³ 93 lbs. | 98 lbs. |
| Front Half | 32 lbs. | 37 lbs. |
| Rear Half | 24 lbs. | 24 lbs. |
| Seat w/Arms | 21 lbs. | 21 lbs. |
| Batteries | 16 lbs./30 lbs. | 16 lbs./30 lbs. |
| Tires: | Solid, low profile | Solid, low profile |
| Front | 7.5" | 7.5" |
| Rear | 8" | 8" |
| Rear Anti-Tip Wheels | 2" | 2" |
| Standard Seat | Stadium Style | Stadium Style |
| Seat Back Height | | |
| - no headrest | 14.75" | 14.75" |
| Width x Depth | 17"x 14.5" | 17"x 14.5" |
| Color | Black Vinyl | Black Vinyl |
| Warranty: | | |
| Frame | Lifetime Warranty | Lifetime Warranty |
| Drive Train | 2 Year Warranty | 2 Year Warranty |
| Electronics ² | 2 Year Warranty | 2 Year Warranty |
| Batteries | 1 Year Warranty | 1 Year Warranty |

^{1.} Battery range at 200 lbs. and will vary due to rider weight, drive surface, terrain, and battery type.





Disassembles into 5 Pieces!

4 Wheel Model Shown



A battery charging port is conveniently located on the tiller under the control panel.



Phone: 800-624-6374 Fax: 800-628-5165 www.goldentech.com



^{2.} Electronics warranty excludes batteries.